

SPECIFICATIONS

MODEL # 3610 LIGHT DUTY STROBE



MODEL	3610	3610-240	3610-12	3610-24
OPERATING VOLTAGE	120 VAC, 50/60Hz	240 VAC, 50/60Hz	+12 VDC	+24 VDC
CURRENT	0.06 A	0.03 A	0.18 A	0.08 A
POWER	7.2 VA	7.2 VA	2.16 VA	1.92 VA
FLASH RATE	80 FPM			
PEAK OUTPUT	100,000 Candela			
LAMP LIFE	4,000 Hours			
LENS COLORS	Amber, Blue, Green, Red	Amber, Blue, Clear, Green, Red	Amber, Blue, Green, Red	Amber, Blue, Green, Red
DIMENSIONS	5.25" H x 5.5" DIA. (133.4 mm X 139.7 mm)		5.06" H x 5.5" DIA. (128.5 mm X 139.7 mm)	
MOUNTING	1/2" NPT pipe mount		Surface mount	
ENVIRONMENTAL	Indoor/outdoor use. NEMA 3R enclosure Operating Temperature: -31° to 150° F (-35° to 66° C)			
CERTIFICATIONS	UL Listed and CSA Certified			
NET WEIGHT	0.9 LBS (0.4 KG)		0.8 LBS (0.4 KG)	
SHIPPING WEIGHT	1.4 LBS (0.5 KG)		1.3 LBS (0.5 KG)	