

## SPECIFICATIONS

### MODEL # 3602 ELECTRONIC SIREN



MODEL	3602	3602-230	3602-24
OPERATING VOLTAGE	120 VAC, 50/60Hz	240 VAC, 50/60Hz	+24 VDC
CURRENT	0.21 A	0.12 A	0.6 A
POWER	25.2 VA	28.8 VA	14.4 VA
OUTPUT AT 10 FT (3.05 m)	107 to 111 dB		
OUTPUT AT 30 FT (9.15 m)	97 to 101 dB		
OUTPUT AT 70 FT (21.34 m)	90 to 94 dB		
OUTPUT AT 100 FT (30.48 m)	87 to 91 dB		
MATERIAL AND FINISH	Impact and UV resistant plastic		
TONE SELECTION	Three options - wail, yelp, and horn – user selectable		
DIMENSIONS	8.9" H x 12.1" W x 14.5" D (226.1mm x 307.3mm x 368.3 mm) w/o backbox		
MOUNTING	Omni-directional swivel mount		
ENVIRONMENTAL	Indoor and outdoor use. Type 3R enclosure. Operating Temperature: -31° to 151° F (-35° to 66° C)		
CERTIFICATIONS	UL and cUL Listed		
NET WEIGHT	4.4 lbs (2.0 kg) w/o backbox		
SHIPPING WEIGHT	5.2 lbs (2.4 kg) w/o backbox		